Package 'scCAN'

November 4, 2026

Type Package

Title Single-Cell Clustering using Autoencoder and Network Fusion

Version 1.0.6

Maintainer Bang Tran <s.tran@csus.edu>

Description A single-cell Clustering method using 'Autoencoder' and Network fusion ('scCAN') Bang Tran (2022) <doi:10.1038/s41598-022-14218-6> for segregating the cells from the high-dimensional 'scRNA-Seq' data. The software automatically determines the optimal number of clusters and then partitions the cells in a way such that the results are robust to noise and dropouts. 'scCAN' is fast and it supports Windows, Linux, and Mac OS.

License LGPL

Encoding UTF-8

LazyData true

LazyDataCompression xz

Depends R (>= 4.2.0), scDHA (>= 1.2.0), FNN, purrr

Imports stats, parallel

RoxygenNote 7.3.1

URL https://github.com/bangtran365/scCAN

BugReports https://github.com/bangtran365/scCAN/issues

Suggests knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation no

Author Bang Tran [aut, cre],
Duc Tran [aut],
Hung Nguyen [aut],
Tin Nguyen [fnd]

Repository CRAN

Date/Publication 2026-11-04 10:00:02 UTC

Contents

adjustedRandIndex 2
calculate_celltype_prob 2
curate_markers 3
find_markers 4
find_specific_marker 4
get_cluster_markers 5
scCAN 5
SCE 7

Index **8**

`adjustedRandIndex` *adjustedRandIndex*

Description

The function to calculate adjusted Rand index value with the inputs of true clusters and predicted clusters

Usage

```
adjustedRandIndex(x, y)
```

Arguments

x	A vector that contain predicted cluster assignment.
y	A vector that contain true cluster assignment.

Value

An value number ranging from 0 to 1 where 1 indicates a perfect clustering result and 0 means random partition.

`calculate_celltype_prob` *calculate_celltype_prob*

Description

Calculate clusters and cell types similarity based on the markers.

Usage

```
calculate_celltype_prob(clt_marker_list, marker_database_list, type = "jacc")
```

Arguments

`clt_marker_list`
: A list of markers for all cluster.

`marker_database_list`
: A list of markers of all reference cell types.

`type`
: A parameter to select the method to measure cluster and cell type similarity

- jacc - Jaccard index.
- ac - Accuracy.
- f1 - F1 score.

.

Value

A confusion matrix between clusters and cell types. Each cell represents a probabilty of a cluster belongs to a cell type.

`curate_markers` *curate_markers*

Description

Filter genes that have low p-value and fold-change.

Usage

```
curate_markers(
  whole_list,
  gene_names,
  wilcox_threshold = 0.001,
  logfc_threshold = 1.5
)
```

Arguments

`whole_list`
: A list of markers for all clusters.

`gene_names`
: All the gene names of the expression matrix.

`wilcox_threshold`
: A threshold for p-value `wilcox_threshold = 0.001` by default.

`logfc_threshold`
: A threshold for fold-change `logfc_threshold = 1.5` by default.

Value

A list of markers that are strong expressed for discovered clusters.

find_markers *find_markers*

Description

Perform cluster-wise Wilcox test and fold-change for each gene.

Usage

```
find_markers(input_data_matrix, cluster_labels, identity = 1, threads = 8)
```

Arguments

input_data_matrix	An expression matrix in which rows are genes and columns are cells.
cluster_labels	A vector of cluster labels obtained from clustering methods.
identity	A parameter to select specific cluster identity = 1 by default.
threads	A parameter to control number of cores used for analysis threads = 1 by default.

Value

A list that contains p-value and fold-change ratio for all genes of each cluster.

find_specific_marker *find_specific_marker*

Description

Calculate cluster and cell type similarity based on the markers.

Usage

```
find_specific_marker(gene_name, f_list, type = "jacc")
```

Arguments

gene_name	A list of markers belong to the cluster.
f_list	A list of markers belongs to a reference cell type.
type	A parameter to select the method to measure cluster and cell type similarity • jacc - Jaccard index. • ac - Accuracy. • f1 - F1 score. .

Value

A vector of probabilties of a cluster belongs to cell types.

`get_cluster_markers` *get_cluster_markers*

Description

Find markers for each cluster

Usage

```
get_cluster_markers(input_data_matrix, labels_vector, threads = 1)
```

Arguments

`input_data_matrix`	An expression matrix in which rows are genes and columns are cells.
`labels_vector`	A vector of cluster labels ontained from clustering methods.
`threads`	A parameter to control number of cores used for analysis `threads = 1` by default.

Value

A list that contains markers for each cluster.

`scCAN` *scCAN*

Description

This is the main function to perform sc-RNA seq data clustering clustering. scCAN is fully unsupervised scRNA-seq clustering framework that uses deep neural network and network fusion-based clustering algorithm. First, scCAN applies a non-negative autoencoder to filter scRNA-seq data. Second, the filtered data is passed to stacked Bayesian autoencoder to get multiple low-dimensional representations of input data. Subsequently, scCAN converts these compressed data into networks and unify those networks to a single graph. Then, scCAN uses a spectral clustering algorithm to obtain final clusters assignment.

Usage

```
scCAN(
  data,
  sparse = FALSE,
  n.neighbors = 30,
  alpha = 0.5,
  n.iters = 10,
  ncores = 10,
  r.seed = 1,
  subsamp = TRUE,
  k = 2:15,
  samp.size = 5000
)
```

Arguments

data	Gene expression matrix, with rows represent samples and columns represent genes.
sparse	Boolen variable indicating whether data is a sparse matrix. The input must be a non negative sparse matrix.
n.neighbors	Number of neighboring cells that are used to caculate the edge's weight. The number of neighbors are set n.neighbors = 30 by default.
alpha	A hyper parameter that control the weight of graph. This values is set to alpha = 0.5 by default.
n.iters	A hyper-parameter to set the number of network fusion iterations. It is set to n.iters = 10 by default.
ncores	Number of processor cores to use.
r.seed	A parameter to set a seed for reproducibility. This values is set to r.seed = 1 by default.
subsamp	Enable subsampling process for big data. This values is set to subsamp = TRUE by default.
k	A vector to search for optimal number of cluster.
samp.size	A parameter to control number of sub-sampled cells.

Value

List with the following keys:

- cluster - A numeric vector containing cluster assignment for each sample.
- k - The optimal number of cluster.
- latent - The latent data generated from autoencoders.

References

1. Duc Tran, Hung Nguyen, Bang Tran, Carlo La Vecchia, Hung N. Luu, Tin Nguyen (2021). Fast and precise single-cell data analysis using a hierarchical autoencoder. Nature Communications, 12, 1029. doi: 10.1038/s41467-021-21312-2

Examples

```
## Not run:
# Not run: scDHA requires the 'torch' backend (libtorch) to be installed
# via torch::install_torch(), which is not available on CRAN check machines,
# and the example takes several minutes to complete.
# Load the package and the example data (SCE dataset)
library(scCAN)
#Load example data
data("SCE")

#Get data matrix and label
data <- t(SCE$data); label <- as.character(SCE$cell_type1)

#Generate clustering result, the input matrix has rows as samples and columns as genes
result <- scCAN(data, r.seed = 1)

#Get the clustering result
cluster <- result$cluster

#Calculate adjusted Rand Index
ari <- round(scCAN::adjustedRandIndex(cluster,label), 2)
message(paste0("ARI = ", ari))


## End(Not run)
```

SCE *SCE*

Description

SCE dataset includes scRNA-seq data and cell type information.

Usage

```
SCE
```

Format

An object of class `list` of length 2.

Index

∗ **datasets**
SCE, 7

adjustedRandIndex, 2

calculate_celltype_prob, 2
curate_markers, 3

find_markers, 4
find_specific_marker, 4

get_cluster_markers, 5

scCAN, 5
SCE, 7