

The `hypgtoe` package

Heiko Oberdiek*
<heiko.oberdiek at googlemail.com>

2016/05/16 v0.2

Abstract

Experimental package for links to embedded files.

Contents

1 Documentation	1
1.1 Introduction	1
1.2 User interface	2
1.3 Example	2
2 Implementation	3
2.1 Identification	3
2.2 Load packages	3
2.3 Color support	3
2.4 Extend \href	4
2.5 Implement gotoe action	4
2.6 Keys for gotoe action	5
3 Installation	6
3.1 Download	6
3.2 Bundle installation	6
3.3 Package installation	6
3.4 Refresh file name databases	6
3.5 Some details for the interested	7
4 Catalogue	7
5 References	8
6 History	8
[2007/10/30 v0.1]	8
[2016/05/16 v0.2]	8
7 Index	8

1 Documentation

1.1 Introduction

This is a first experiment for links to embedded files. The package `hypgtoe` is named after the PDF action name `/GoToE`. Feedback is welcome, especially to the user interface.

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

- Currently only embedded files and named destinations are supported.
- Missing are support for destination arrays and attached files.
- Special characters aren't supported either.

In the future the package may be merged into package `hyperref`.

1.2 User interface

`\href` is extended to detect the prefix ‘`gotoe:`’. The part after the prefix is evaluated as key value list from left to right. For details, see “8.5.3 Action Types, Embedded Go-To Actions” [1].

dest: The destination name. The destination name can be set by `\hypertarget` in the target document. Or check the `.aux` file for destination names of `\label` commands. Also the target PDF file can be inspected, look for `/Dests` in the `/Names` entry of the catalog for named destinations. (Required.)

root: The file name of the root document. (Optional.)

parent: Go to the parent document. (No value, optional.)

embedded: Go to the embedded document. The value is the file name as it appears in `/EmbeddedFiles` of the current document.

The colors are controlled by `hyperref`'s options `gotoecolor` and `gotoebordercolor`. They can be set in `\hypersetup`, for example. Default is the color of file links.

1.3 Example

```

1 {*example}
2 \NeedsTeXFormat{LaTeX2e}
3 \RequirePackage{filecontents}
4 \begin{filecontents}{hypgotoe-child.tex}
5 \NeedsTeXFormat{LaTeX2e}
6 \documentclass{article}
7 \usepackage{hypgotoe}[2016/05/16]
8 \begin{document}
9 \section{This is the child document.}
10 \href{gotoe:}
11   dest={page.1},parent%
12 }{Go to first page of main document} \\
13 \href{gotoe:}
14   dest={page.2},parent%
15 }{Go to second page of main document}
16 \newpage
17 \section{This is the second page of the child document.}
18 \href{gotoe:}
19   dest={page.1},parent%
20 }{Go to first page of main document} \\
21 \href{gotoe:}
22   dest={page.2},parent%
23 }{Go to second page of main document}
24
25 \hypertarget{foobar}{}
26 Anker foobar is here.
27 \end{document}
28 \end{filecontents}
29 \documentclass{article}
30 \usepackage{hypgotoe}[2016/05/16]
31 \usepackage{embedfile}
32 \IfFileExists{hypgotoe-child.pdf}{%

```

```

33 \embedfile{hypgtoe-child.pdf}%
34 }%
35 \typeout{%
36 \typeout{--> Run hypgtoe-child.tex through pdflatex}%
37 \typeout{%
38 }
39 \begin{document}
40 \section{First page of main document}
41 \href{gotoe:}{%
42 dest=page.1,embedded=hypgtoe-child.pdf}%
43 }{Go to first page of child document}\\
44 \href{gotoe:}{%
45 dest=page.2,embedded=hypgtoe-child.pdf}%
46 }{Go to second page of child document}\\
47 \href{gotoe:}{%
48 dest=foobar,embedded=hypgtoe-child.pdf}%
49 }{Go to foobar in child document}
50 \newpage
51 \section{Second page of main document}
52 \href{gotoe:}{%
53 dest=section.1,embedded=hypgtoe-child.pdf}%
54 }{Go to first section of child document}\\
55 \href{gotoe:}{%
56 dest=section.2,embedded=hypgtoe-child.pdf}%
57 }{Go to second section of child document}\\
58 \href{gotoe:}{%
59 dest=foobar,embedded=hypgtoe-child.pdf}%
60 }{Go to foobar in child document}
61 \end{document}
62 
```

2 Implementation

2.1 Identification

```

63 <*package>
64 \NeedsTeXFormat{LaTeX2e}
65 \ProvidesPackage{hypgtoe}%
66 [2016/05/16 v0.2 Links to embedded files (HO)]%

```

2.2 Load packages

```

67 \RequirePackage{ifpdf}[2007/09/09]
68 \ifpdf
69 \else
70 \PackageError{hypgtoe}{%
71 Other drivers than pdfTeX in PDF mode are not supported.%
72 \MessageBreak
73 Package loading is aborted%
74 }@\ehc
75 \expandafter\endinput
76 \fi
77 \RequirePackage{pdfescape}[2007/10/27]
78 \RequirePackage{hyperref}[2016/05/16]

```

2.3 Color support

```

79 \define@key{Hyp}{gotoebordercolor}{%
80 \HyColor@HyperrefBordercolor{\#1}%
81 \c@gotoebordercolor{hyperref}{\c@gotoebordercolor}%
82 }%
83 \providecommand*{\c@gotoecolor}{\c@filecolor}%
84 \providecommand*{\c@gotoebordercolor}{\c@filebordercolor}%

```

2.4 Extend \href

```
\@hyper@readexternallink
 85 \def\@hyper@readexternallink#1#2#3#4:#5:#6\\#7{%
 86   \ifx\\#6\\%
 87     \expandafter\@hyper@linkfile file:#7\\{\#3}{\#2}%
 88   \else
 89     \ifx\\#4\\%
 90       \expandafter\@hyper@linkfile file:#7\\{\#3}{\#2}%
 91     \else
 92       \def\@pdftempa{\#4}%
 93       \ifx\@pdftempa\@pdftempwordfile
 94         \expandafter\@hyper@linkfile#7\\{\#3}{\#2}%
 95       \else
 96         \ifx\@pdftempa\@pdftempwordrun
 97           \expandafter\@hyper@launch#7\\{\#3}{\#2}%
 98         \else
 99           \ifx\@pdftempa\@pdftempwordgtoe
100             \hyper@linkgtoe{\#3}{\#5}%
101           \else
102             \hyper@linkurl{\#3}{\#7\ifx\\#2\\\\else\hyper@hash\#2\fi}%
103           \fi
104         \fi
105       \fi
106     \fi
107   \fi
108 }

\@pdftempwordgtoe
109 \def\@pdftempwordgtoe{gtoe}
```

2.5 Implement gotoe action

```
\hyper@linkgtoe
110 \def\hyper@linkgtoe#1#2{%
111   \begingroup
112   \let\HyGoToE@Root\@empty
113   \let\HyGoToE@Dest\@empty
114   \let\HyGoToE@TBegin\@empty
115   \let\HyGoToE@TEnd\@empty
116   \setkeys{HyGoToE}{#2}%
117   \leavevmode
118   \pdfstartlink
119     attr{%
120       \Hy@setpdfborder
121       \ifx\@pdfhighlight\@empty
122         \else
123           /H\@pdfhighlight
124         \fi
125       \ifx\@urlbordercolor\relax
126         \else
127           /C[\@urlbordercolor]%
128         \fi
129     }%
130   user{%
131     /Subtype/Link%
132     /A<<%
133       /Type/Action%
134       /S/GoToE%
135       \Hy@SetNewWindow
136       \HyGoToE@Root
137       \HyGoToE@Dest
```

```

138      \HyGoToE@TBegin
139      \HyGoToE@TEnd
140      >>%
141      }%
142      \relax
143      \Hy@colorlink\@gotoecolor#1%
144      \close@pdfink
145      \endgroup
146 }

```

2.6 Keys for gotoe action

```

147 \define@key{HyGoToE}{root}{%
148   \EdefEscapeString\HyGoToE@temp{\#1}%
149   \edef\HyGoToE@Root{%
150     /F<<%
151     /Type/Filespec%
152     /F(\HyGoToE@temp)%
153   >>%
154 }%
155 }
156 \define@key{HyGoToE}{dest}{%
157   \EdefEscapeString\HyGoToE@temp{\#1}%
158   \edef\HyGoToE@Dest{%
159     /D(\HyGoToE@temp)%
160   }%
161 }
162 \define@key{HyGoToE}{parent}{%
163   \def\HyGoToE@temp{\empty}
164   \ifx\HyGoToE@temp\empty
165   \else
166     \PackageWarning{hypgtoe}{Ignore value for `parent'}%
167   \fi
168   \edef\HyGoToE@TBegin{%
169     \HyGoToE@TBegin
170     /T<<%
171     /R/P%
172   }%
173   \edef\HyGoToE@TEnd{%
174     \HyGoToE@TEnd
175   >>%
176 }%
177 }
178 \define@key{HyGoToE}{embedded}{%
179   \EdefEscapeString\HyGoToE@temp{\#1}%
180   \edef\HyGoToE@TBegin{%
181     \HyGoToE@TBegin
182     /T<<%
183     /R/C%
184     /N(\HyGoToE@temp)%
185   }%
186   \edef\HyGoToE@TEnd{%
187     \HyGoToE@TEnd
188   >>%
189 }%
190 }
191 </package>

```

3 Installation

3.1 Download

Package. This package is available on CTAN¹:

`CTAN:macros/latex/contrib/oberdiek/hypgotoe.dtx` The source file.

`CTAN:macros/latex/contrib/oberdiek/hypgotoe.pdf` Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

`CTAN:install/macros/latex/contrib/oberdiek.tds.zip`

TDS refers to the standard “A Directory Structure for TeX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

3.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDs:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain TeX:

```
tex hypgotoe.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>hypgotoe.sty</code>	→ <code>tex/latex/oberdiek/hypgotoe.sty</code>
<code>hypgotoe.pdf</code>	→ <code>doc/latex/oberdiek/hypgotoe.pdf</code>
<code>hypgotoe-example.tex</code>	→ <code>doc/latex/oberdiek/hypgotoe-example.tex</code>
<code>hypgotoe.dtx</code>	→ <code>source/latex/oberdiek/hypgotoe.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

3.4 Refresh file name databases

If your TeX distribution (teTeX, mikTeX, ...) relies on file name databases, you must refresh these. For example, teTeX users run `texhash` or `mktexlsr`.

¹<http://ctan.org/pkg/hypgotoe>

3.5 Some details for the interested

Unpacking with L^AT_EX. The .dtx chooses its action depending on the format:

plain T_EX: Run docstrip and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for docstrip (really, docstrip does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{hypgtoe.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the .dtx or the .drv to generate the documentation. The process can be configured by the configuration file ltxdoc.cfg. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex hypgtoe.dtx
makeindex -s gind.ist hypgtoe.idx
pdflatex hypgtoe.dtx
makeindex -s gind.ist hypgtoe.idx
pdflatex hypgtoe.dtx
```

4 Catalogue

The following XML file can be used as source for the T_EX Catalogue. The elements **caption** and **description** are imported from the original XML file from the Catalogue. The name of the XML file in the Catalogue is **hypgtoe.xml**.

```
192 <catalogue>
193 <?xml version='1.0' encoding='us-ascii'?>
194 <!DOCTYPE entry SYSTEM 'catalogue.dtd'>
195 <entry datestamp='$Date$' modifier='$Author$' id='hypgtoe'>
196   <name>hypgtoe</name>
197   <caption>Links to embedded files.</caption>
198   <authorref id='auth:oberdiek' />
199   <copyright owner='Heiko Oberdiek' year='2007' />
200   <license type='lppl1.3' />
201   <version number='0.2' />
202   <description>
203     This experimental package is a first experiment for links to embedded
204     files. It is named after the PDF action name <tt>/GoToE</tt>.
205   <p/>
206   The package is part of the <xref refid='oberdiek'>oberdiek</xref>
207   bundle.
208 </description>
209 <documentation details='Package documentation'
210   href='ctan:/macros/latex/contrib/oberdiek/hypgtoe.pdf' />
211 <ctan file='true' path='/macros/latex/contrib/oberdiek/hypgtoe.dtx' />
212 <miktex location='oberdiek' />
213 <texlive location='oberdiek' />
214 <install path='/macros/latex/contrib/oberdiek/oberdiek.tds.zip' />
215 </entry>
216 </catalogue>
```

5 References

- [1] Adobe Systems Incorporated: *PDF Reference, Sixth Edition, Version 1.7*, Oktober 2006; http://www.adobe.com/devnet/pdf/pdf_reference.html.

6 History

[2007/10/30 v0.1]

- First experimental version.

[2016/05/16 v0.2]

- Documentation updates.

7 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	
\@ehc	74
\@empty	112, 113, 114, 115, 121, 164
\@filebordercolor	84
\@filecolor	83
\@gotobordercolor	81, 84
\@gotocolor	83, 143
\@hyper@launch	97
\@hyper@linkfile	87, 90, 94
\@hyper@readexternallink	85
\@pdfhighlight	123
\@pdfhighlight	121
\@pdftempa	92, 93, 96, 99
\@pdftempwordfile	93
\@pdftempwordgtoe	99, 109
\@pdftempwordrun	96
\@curlbordercolor	125, 127
\`	12, 20, 43, 46, 54, 57, 85, 86, 87, 89, 90, 94, 97, 102
B	
\begin	4, 8, 39
C	
\close@pdflink	144
D	
\define@key	79, 147, 156, 162, 178
\documentclass	6, 29
E	
\EdefEscapeString	148, 157, 179
\embedfile	33
\end	27, 28, 61
\endinput	75
H	
\href	10, 13, 18, 21, 41, 44, 47, 52, 55, 58
\Hy@colorlink	143
\Hy@SetNewWindow	135
I	
\Hy@setpdfborder	120
\HyColor@HyperrefBordercolor	80
\HyGoToE@Dest	113, 137, 158
\HyGoToE@Root	112, 136, 149
\HyGoToE@TBegin	114, 138, 168, 169, 180, 181
\HyGoToE@Temp	148, 152, 157, 159, 163, 164, 179, 184
\HyGoToE@TEnd	115, 139, 173, 174, 186, 187
\hyper@hash	102
\hyper@linktoe	100, 110
\hyper@linkurl	102
\hypertarget	25
L	
\IfFileExists	32
\ifpdf	68
\ifx	86, 89, 93, 96, 99, 102, 121, 125, 164
M	
\MessageBreak	72
N	
\NeedsTeXFormat	2, 5, 64
\newpage	16, 50
P	
\PackageError	70
\PackageWarning	166
\pdfstartlink	118
\providecommand	83, 84
\ProvidesPackage	65
R	
\RequirePackage	3, 67, 77, 78

S	T
\section	9, 17, 40, 51
\setkeys	116 \usepackage
	7, 30, 31