

CSS selectors

Needed or not?

Supported methods

Filtering classes

Filtering attributes

Combining methods

Child selectors

Simple formulas

Special cases

Combinations

Comparison (1)

Comparison (2)

- used in HTML styling
- a bit different from the path based method
- shortcuts for filtering by attribute
- class filtering is special because it checks for list
- one can select more at the same time
- performance is okay compared to path lookup
- selectors go between curly braces:

```
\xmlall {#1} {{foo bar .whatever, bar foo .whatever}}
```

Needed or not?

The following methods are supported:

element	all tags element
element-1 > element-2	all tags element-2 with parent tag element-1
element-1 + element-2	all tags element-2 preceded by tag element-1
element-1 ~ element-2	all tags element-2 preceded by tag element-1
element-1 element-2	all tags element-2 inside tag element-1
[attribute]	has attribute
[attribute=value]	attribute equals value
[attribute~=value]	attribute contains value (space is separator)
[attribute^="value"]	attribute starts with value
[attribute\$="value"]	attribute ends with value
[attribute*="value"]	attribute contains value
.class	has class
#id	has id
:nth-child(n)	the child at index n
:nth-last-child(n)	the child at index n from the end
:first-child	the first child
:last-child	the last child
:nth-of-type(n)	the match at index n
:nth-last-of-type(n)	the match at index n from the end
:first-of-type	the first match
:last-of-type	the last match
:only-of-type	the only match or nothing
:only-child	the only child or nothing
:empty	only when empty
:root	the whole tree

Supported methods

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

.one

b.one
b.one.two
g gg f.one
g f.one

Filtering classes

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

— .one, .two —

b.one
b.two
b.one.two
g gg f.one
g gg f.two
g f.one

Filtering classes

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

—— .one, .two, #first ———

b.one
b.two
b.one.two
b#first
g gg f.one
g gg f.two
g f.one

Filtering classes

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

```
— [foo], [bar=foo] —
```

```
@foo = bar
@bar = foo
```

Filtering attributes

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>

—— [bar~=foo] ————
```

@bar = foo

Filtering attributes

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

— [bar^="foo"] —

```
@bar = foo
@bar = fool
@bar = foo2
@bar = foo3
@bar = foo+4
```

Filtering attributes

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>

— [whatever~="five"] ——————
```

@whatever = four five six

Filtering attributes

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

— g f .one, g f .three —

g gg f.one
g gg f.three
g f.one
g f.three

Combining methods

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

— g > f .one, g > f .three —

g f.one
g f.three

Combining methods

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

— d + e —

d e

Combining methods

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

— d e —

d e
d e e

Combining methods

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

— d e, g f .one, g f .three —

d e
d e e
g gg f.one
g gg f.three
g f.one
g f.three

Combining methods

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

— a:nth-child(3) —

b.one.two

Child selectors

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

— a:nth-last-child(3) —

```
<f class="one">g f.one</f>
```

Child selectors

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

```
— g:nth-of-type(3) —
```

```
<gg><f>g gg f</f></gg>
```

Child selectors

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

```
— g:nth-last-of-type(3) —
```

```
<gg><f class="three">g gg f.three</f></gg>
```

Child selectors

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

— a:first-child —

b.one

Child selectors

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

— a:last-child —

```
@whatever = four five six
```

Child selectors

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

— e:first-of-type —

d e

Child selectors

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

— gg d:only-of-type —

g gg d

Child selectors

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

— a:nth-child(even) —

b.two
b.three
c
d e
d f
@bar = foo
@bar = foo2
@bar = foo+4
<gg><d>g gg d</d></gg>

Simple formulas

```
<gg><f class="one">g gg f.one</f></gg>
<gg><f class="two">g gg f.two</f></gg>
<f class="one">g f.one</f>
```

Simple formulas

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="foo1">@bar = foo1</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

```
—— a:nth-child(odd) ———
```

b.one
b.one.two
b#first
d e
d e e
@foo = bar
@bar = foo1
@bar = foo3
g
<gg><f>g gg f</f></gg>

Simple formulas

```
g  
<gg><f class="three">g gg f.three</f></gg>  
<f class="three">g f.three</f>
```

Simple formulas

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="foo1">@bar = foo1</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

—— a:nth-child(3n+1) ———

b.one
b.two
b.one.two
b.three
b#first
c
d e
d e
d e e
d f

Simple formulas

```
@foo = bar
@bar = foo
@bar = foo1
@bar = foo2
@bar = foo3
@bar = foo+4
g
<gg><d>g gg d</d></gg>
<gg><f>g gg f</f></gg>
<gg><f class="one">g gg f.one</f></gg>
g
<gg><f class="two">g gg f.two</f></gg>
<gg><f class="three">g gg f.three</f></gg>
```

Simple formulas

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

— a:nth-child(2n+3) —

b.one.two
c
d e e
@bar = foo
@bar = foo3
<gg><d>g gg d</d></gg>
g
<f class="one">g f.one</f>

Simple formulas

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

— g:empty —

Special cases

```

<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="foo1">@bar = foo1</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>

```

— g:root —————

```

  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>

```

Special cases

```
<f foo="bar">@foo = bar</f>
<f bar="foo">@bar = foo</f>
<f bar="foo1">@bar = foo1</f>
<f bar="foo2">@bar = foo2</f>
<f bar="foo3">@bar = foo3</f>
<f bar="foo+4">@bar = foo+4</f>
<g>g</g>
<g><gg><d>g gg d</d></gg></g>
<g><gg><f>g gg f</f></gg></g>
<g><gg><f class="one">g gg f.one</f></gg></g>
<g>g</g>
<g><gg><f class="two">g gg f.two</f></gg></g>
<g><gg><f class="three">g gg f.three</f></gg></g>
<g><f class="one">g f.one</f></g>
<g><f class="three">g f.three</f></g>
<h whatever="four five six">@whatever = four five six</h>
```

Special cases

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="foo1">@bar = foo1</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

```
* _____
```

```
<b class="one">b.one</b>
<b class="two">b.two</b>
<b class="one two">b.one.two</b>
<b class="three">b.three</b>
<b id="first">b#first</b>
<c>c</c>
<d>d e</d>
<e>d e</e>
<e>d e e</e>
<d>d f</d>
```

Special cases

```

<f foo="bar">@foo = bar</f>
<f bar="foo">@bar = foo</f>
<f bar="foo1">@bar = foo1</f>
<f bar="foo2">@bar = foo2</f>
<f bar="foo3">@bar = foo3</f>
<f bar="foo+4">@bar = foo+4</f>
<g>g</g>
<g><gg><d>g gg d</d></gg></g>
<g><gg><f>g gg f</f></gg></g>
<g><gg><f class="one">g gg f.one</f></gg></g>
<g>g</g>
<g><gg><f class="two">g gg f.two</f></gg></g>
<g><gg><f class="three">g gg f.three</f></gg></g>
<g><f class="one">g f.one</f></g>
<g><f class="three">g f.three</f></g>
<h whatever="four five six">@whatever = four five six</h>

b.one
b.two
b.one.two
b.three
b#first
c
d e
d e
d e e
d f
@foo = bar
@bar = foo
@bar = foo1
@bar = foo2
@bar = foo3
@bar = foo+4
g
<gg><d>g gg d</d></gg>
<d>g gg d</d>
g gg d
<gg><f>g gg f</f></gg>
<f>g gg f</f>
g gg f
<gg><f class="one">g gg f.one</f></gg>
<f class="one">g gg f.one</f>
g gg f.one

```

Special cases

```
g
<gg><f class="two">g gg f.two</f></gg>
<f class="two">g gg f.two</f>
g gg f.two
<gg><f class="three">g gg f.three</f></gg>
<f class="three">g gg f.three</f>
g gg f.three
<f class="one">g f.one</f>
g f.one
<f class="three">g f.three</f>
g f.three
@whatever = four five six
```

Special cases

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

— g gg f .one —

g gg f.one

Combinations

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

```
— g/gg/f[@class='one'] —
```

```
g gg f.one
```

Combinations

```
<?xml version="1.0" ?>

<a>
  <b class="one">b.one</b>
  <b class="two">b.two</b>
  <b class="one two">b.one.two</b>
  <b class="three">b.three</b>
  <b id="first">b#first</b>
  <c>c</c>
  <d>d e</d>
  <e>d e</e>
  <e>d e e</e>
  <d>d f</d>
  <f foo="bar">@foo = bar</f>
  <f bar="foo">@bar = foo</f>
  <f bar="fool">@bar = fool</f>
  <f bar="foo2">@bar = foo2</f>
  <f bar="foo3">@bar = foo3</f>
  <f bar="foo+4">@bar = foo+4</f>
  <g>g</g>
  <g><gg><d>g gg d</d></gg></g>
  <g><gg><f>g gg f</f></gg></g>
  <g><gg><f class="one">g gg f.one</f></gg></g>
  <g>g</g>
  <g><gg><f class="two">g gg f.two</f></gg></g>
  <g><gg><f class="three">g gg f.three</f></gg></g>
  <g><f class="one">g f.one</f></g>
  <g><f class="three">g f.three</f></g>
  <h whatever="four five six">@whatever = four five six</h>
</a>
```

— g/gg f .one —————

g gg f.one

Combinations

```
<?xml version="1.0" ?>

<document>
    <title class="one"  >title 1</title>
    <title class="two"  >title 2</title>
    <title class="one"  >title 3</title>
    <title class="three">title 4</title>
</document>
```

— document title .one, document title .three —————

```
title 1
title 3
title 4
```

Comparison (1)

```
<?xml version="1.0" ?>

<document>
    <title class="one"  >title 1</title>
    <title class="two"  >title 2</title>
    <title class="one"  >title 3</title>
    <title class="three">title 4</title>
</document>
```

—— /document/title[(@class='one') or (@class='three')] -----

title 1
title 3
title 4

Comparison (1)

```
<?xml version="1.0" ?>

<document>
  <title    class="one">title 1</title>
  <subtitle class="sub">title 1.1</subtitle>
  <title    class="two">title 2</title>
  <subtitle class="sub">title 2.1</subtitle>
  <title    class="one">title 3</title>
  <subtitle class="sub">title 3.1</subtitle>
  <title    class="two">title 4</title>
  <subtitle class="sub">title 4.1</subtitle>
</document>
```

— document title .one + subtitle, document title .two + subtitle

title 1.1
title 2.1
title 3.1
title 4.1

A combined filter triggers a sorting pass!

Comparison (2)